

A COMPARATIVE INVESTIGATION OF 13-LEVEL, 23-LEVEL AND 33-LEVEL CONVENTIONAL CASCADED H-BRIDGE MULTILEVEL INVERTERS BY USING SIMULINK / MATLAB

DODDA SATISH REDDY¹, TEWODROS DEGU KEBEDE², BIKS ALEBACHEW TAYE³ &
CHAKRALA KRISHNA PRASAD⁴

^{1, 2, 3}Department of ECE, Debre Tabor University, Debre Tabor, Amhara Region, Ethiopia

⁴Department of EEE, KITS Engineering College, Khammam, Telangana, India

ABSTRACT

This paper aims to extend the knowledge about performance of different Cascade H-Bridge multilevel inverters (CHB-MLI) through harmonic analysis. Large utility applications require advanced power electronics converter to meet high power demands. As a result, multilevel power converter structure has been introduced as an alternative for high power and medium voltage situations. A multilevel converter not only achieves high power ratings, but also improves performance of the whole system in terms of harmonics, dv/dt stresses, and stresses in the bearings of a motor [1].

Multilevel inverters are becoming more popular in the power conversion systems for high power and power quality demanding applications. The MATLAB based simulation on SIMULINK platform is presented for Cascade H-Bridge multilevel inverter (CHB-MLI) topology of Single Phase cascaded H-bridge Multilevel Inverter for 13, 23, and 33-levels. A detailed comparison of Cascade H-Bridge multilevel inverters (CHB-MLI) are presented in the paper based on number of power devices used, Total Harmonic Distortion [1].

KEYWORDS: Cascade H-Bridge Multilevel Inverter (CHB-MLI), Flying Capacitor Multilevel Inverter (FC-MLI), Neutral Point Clamped Multilevel Inverter (NPC-MLI), Total Harmonic Distortion (THD)